

File 347:JAPIO Oct 1976-2002/Aug(Updated 021203)

(c) 2002 JPO & JAPIO

\*File 347: JAPIO data problems with year 2000 records are now fixed.

Alerts have been run. See HELP NEWS 347 for details.

# Set Items Description

-----

?s pn=jp 1125613

S2 1 PN=JP 1125613

?t 2/9/1

2/9/1

DIALOG(R)File 347:JAPIO

(c) 2002 JPO & JAPIO. All rts. reserv.

02828013 \*\*Image available\*\*

SEE-THROUGH TYPE TOUCH PANEL DEVICE DOUBLING AS KEYBOARD

PUB. NO.: 01-125613 [ JP 1125613 A]

PUBLISHED: May 18, 1989 (19890518)

INVENTOR(s): HAYASHI YUJI

MIZUNO TOSHIKI

APPLICANT(s): BROTHER IND LTD [000526] (A Japanese Company or Corporation),

JP (Japan)

APPL. NO.: 62-283778 [JP 87283778]

FILED: November 10, 1987 (19871110)

INTL CLASS: [4] G06F-003/023; G06F-003/03; G06F-003/033

JAPIO CLASS: 45.3 (INFORMATION PROCESSING -- Input Output Units)

JAPIO KEYWORD:R131 (INFORMATION PROCESSING -- Microcomputers &

Microprocessors)

JOURNAL: Section: P, Section No. 919, Vol. 13, No. 368, Pg. 132,

August 16, 1989 (19890816)

## ABSTRACT

PURPOSE: To use a see-through type touch panel as a keyboard and to realize the input processing for a large quantity of information with reduced fatigue by attaching an attachable/detachable structure of the touch panel to a display device and then putting an information display means on the display device after removal of the touch panel.

CONSTITUTION: In a normal state a keyboard stage 3 is stored into a storing space 10 of a case 5 and the display data are selected with push of a prescribed position of a see-through type touch panel 1 set at the front of a CRT 4. When the panel 1 is used as a keyboard type input device, the stage 3 is drawn out toward an arrow AR and a roller 13 is set at the front recess part of the space 10. In this case, the tip boss of an arm 2b moves along a guide groove 11 and a support board 2 attached with the panel 1 is set on the stage 3. Thus the panel 1 can be used as a normal keyboard type input device.